

MEGASPIN FAST TOUCH LITE

WHEEL BALANCER

FAST TOUCH TECHNOLOGY IN A SPACE-SAVING FORMAT

The megaspin Fast Touch Lite builds on the successful technology of the megaspin Fast Touch, offering unparalleled convenience and efficiency to both mobile services and workshops with space constraints.

OPTIONAL CONFIGURATION

The basic FastTouch Lite comprises a stand-alone unit which can be independently fixed to multiple rigid surfaces for the ultimate space saving balancing solution. It is also available with an optional ultra-compact baseplate, allowing for easy installation in workshops with limited space or in mobile fitting vans.



KEY FEATURES

- Virtual Sonar
- One Weight Balancing
- Automatic Approach system
- Electric brake



SPECIFICATIONS

Single phase power supply:	230V/1ph/50-60 hz, 115V/1ph/50-60 Hz
Max. absorbed power:	0,65 kW
Balancing speed:	100 rpm
Cycle time for 15 kg wheel:	4.7 s
Measurement uncertainty:	± 1 g
Resolution:	1 g
Average noise:	< 70 dB (A)
Rim width range:	1.5" - 20" (40mm-510 mm)
Rim diameter range:	10" - 30" (265 mm-765 mm)
Max. wheel weight:	< 75 kg
Machine weight:	30 kg

